

### Key Features

- 5MP Ultra HD Resolution
- H.265 Video Compression
- 20m IR Night Vision
- 2.8mm Wide Angle Lens
- AI Smart Detection
- Triple Stream



### Camera Specifications

#### Video

Imaging Device	1/2.7"
Effective Pixels	5MP 2880 (H) x1620 (V)
Scanning System	Progressive CMOS
Min. Illumination	Color 0.004lux @ F1.6(AGC ON) ; B/W 0 lux @ IR ON

#### Lens Type


Focal Length (Zoom Ratio)	2.8mm
Max. Aperture Ratio	F No. 1.6
Angular Field of View	Horizontal: 110°, Vertical: 58°, Diagonal: 133°
Min. Object Distance	1.8M
Lens Type	Fixed(M12)

#### Operational

IR Viewable Length	Up to 20m
Camera Title	On/Off
Day & Night	IR cut filter with auto switch (Day/Night/Auto/Image/Schedule)
Backlight Compensation	Off/On (5 Zone)
Wide Dynamic Range	WDR
Digital Noise Reduction	3D DNR
Motion Detection	Off/On (8 Level)
Privacy Masking	Off/On (4 Zone, Rectangle)
Gain Control	Auto
White Balance	Auto/Manual
Electronic Shutter Speed	1/5 ~ 1/20000s
On-Board Storage	Micro SD slot, up to 256GB
Alarm	NA
Audio	1 input (RCA), 1 output (RCA)

Hardware Reset	Yes
Smart Feature	Face Detection, Pedestrian & Vehicle , Perimeter Intrusion , Line Crossing , Object Detection, Crossing Counting, Heat Map, Crowd Density , Queue Length , License Plate , Rare Sound, Intrusion, Region Entrance, Region Exiting
<b>Network</b>	
Ethernet	RJ45(10/100BASE-T)
Video Compression Format	H.265/H.264
Resolution	<b>Main Stream@30fps</b> 5MP(2880x1620),4MP(2560x1440) 3MP(2304x1296),1080P(1920x1080) 720P(1280x720) <b>Sub Stream@30fps</b> 720P(1280x720),VGA(640x480),QVGA(320x240) <b>Mobile Stream@30fps</b> VGA(640x480), QVGA (320x240)
Video Quality Adjustment	256Kbps ~ 8Mbps
Bitrate control method	CBR/VBR
Streaming Capability	Triple-Stream(Main/Sub/Mobile)
Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS,RTP/RTSP, SMTP,NTP,UPnP,SNMP,HTTPS,FTP
Web browser	IE10/11 Safari V12.1 above Firefox V.52 above Google chrome V.57 above Edge V.79 above
Security	IP address filter;complicated password;Authenticated username and password
Streaming Method	Unicast/Multicast
Application Programming Interface	ONVIF( Profile S/G/T/M)
<b>Environmental</b>	
Operating Conditions	-30 ~ +55°C/less than ≤ 90% RH
Ingress Protection	NA
<b>Electrical</b>	
Input Voltage / Current	D12V/POE(IEEE802.3af)
Power Consumption ( IR OFF)	2W-3W
Power Consumption ( IR ON)	3.5W-5W
<b>Mechanical</b>	
Material	Plastics
Dimensions (HxWxD)	115*91.6mm
Weight	306g

## Dimension



## Accessory

