ARIN**VIS**

Model: ARC-57VA

Key Features

- **Up to 12MP IP Camera Support**
- **640Mbps Incoming / Outgoing Bandwidth**
- **H.265 / H.265+ Efficient Compression**
- **16CH Synchronous Playback**
- **AI Smart Video Analytics**
- **4× SATA HDD up to 18TB**
- **8K HDMI Video Output**
- **Remote Monitoring via Mobile App**

Camera Specifications

VIDEO

Video	Resolution		12MP, 8MP, 5MP, 3MP, 2MP(1080P), 1.3MP(960P), 1.0MP(720P)
Recording Bandwidth	Inputs		640M
	Outputs		640M

PERFORMANCE

	Compression		Audio: G.711A / G.711U Video: H.264 / H.265 / H.264+ / H.265+
	Frame Rate		4K: 240fps | 4MP: 480fps | 2MP: 960fps
Live/Playback	Event		MD (Sensitivity Level 1~8), Video Loss, Beep, Email, Push Notification to Mobile APP
	Playback Function		Fast forward/backward (2x, 4x, 8x, 16x) | Slow forward (1/2x, 1/4x, 1/8x, 1/16x)
	Playback		Max 16CH playback
	Fisheye		Support
UI/Monitoring	Local		UI 5.0
	WEB		IE10/11 | Safari V12.1+ | Firefox V52+ | Google Chrome V57+ | Edge V79+

	Mobile Viewer		Rxcamview
AI			
AI			Face Detection | Pedestrian Detection | Vehicle Detection | Cross Counting | Heat Map | Crowd Density Detection | Perimeter Intrusion Detection | Line Crossing Detection | Queue Length Detection | License Plate Detection | Rare Sound Detection
INTERFACE			
Interface	P/W Reset		YES
	HDMI		3× (1024×768, 1280×720, 1280×1024, 1440×900, 1920×1080, 1600×1200, 1920×1200, 3840×2160 / 7680×4320 / EDID) Async out *If HDMI 1 output is set to 8K, HDMI 3 & 4 max = 1080P, HDMI 2 disabled. 1× (1024×768, 1280×720, 1280×1024, 1440×900, 1920×1080 / EDID) Async out
	Ethernet		2× RJ45 1000 Base-T
	USB		USB2.0 ×1 (front) | USB3.0 ×2 (rear)
	Audio Out		1
	E-SATA		1
	HDD		4× SATA HDD, up to 18TB (Enterprise-Class)
	Line In		1
	RS485		1
	Alarm Input/Output		16 in / 1 out
GENERAL			
General	OSD Language		English, French, Spanish, Portuguese, German, Italian, Greek, Danish, Finnish, Russian, Hebrew, Turkish, Bulgarian, Arabic, Korean, Japanese, Thai, Hindi, Romanian, Dutch, Polish
	Dimension (W×D×H)		378 × 325.8 × 66 mm
	Input Voltage/Current		12V / 5A
	Power Consumption	(excluding HDD)	9W
	Operating Temperature		-10°C ~ +50°C (14°F ~ 122°F)
	Humidity		Less than 90% RH

378mm (14.9")

66mm (2.6")

PWR   HDD

LOGO Network Video Recorder

325.8m (12.8")

66mm (2.6")